






MOBIHEL®

... for the cars we love

HYDRO CLEAR BASE

For painting of MOBIHEL HYDRO Base with fade out technique.
It helps achieve a smooth homogeneous overspray area in the fade-out zone,
avoiding dark edges around the repair area.



PACKING DATA	Packing: 6 x 0.5 l	Index: 41959721
HYGIENE & PERSONAL PROTECTION		
TECHNICAL CHARACTERISTICS	<p>Colour: Colourless</p> <p>Product type: Polyurethane water dispersions</p> <p>Density: 1,030 g/ml</p>  <p>2004/42/II B(d) (420) 351 EU limit value VOC for this type of products (category II B (d)) in the form, which is ready for application is 420 g/l VOC of this product, prepared for use is 720 g/l.</p>	
SUBSTRATE PREPARATION	<p>Clean surface thoroughly with MOBIHEL HYDRO Cleaner. Spray MOBIHEL HYDRO Clear base wet to vicinity of damaged part, then spray over wet HYDRO Clear base and than MOBIHEL HYDRO Base in a desired colour . By this we assure a suitable orientation of effective pigments.</p>	
APPLICATION	 <p>Application with spray gun:</p> <p>STEP1: MOBIHEL HYDRO CLEAR BASE – ready to use 1,2 – 1,3 mm 2 bar 1 wet layer</p>  <p>Application with spray gun:</p> <p>STEP 2: MOBIHEL HYDRO BASE 1,3 – 1,4 mm 2 - 2,5 bar 2 full layers = 15 – 22 µm</p>  <p>Flash off: 10 - 15 min /20°C</p>	
FURTHER TREATMENT	 <p>Further treatment: MOBIHEL 2K HS CLEARCOATS DH LOW VOC</p>	
SHELF LIFE	 <p>Shelf life: 2 years</p>	
SAFETY ADVICE	<p>IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>ONLY FOR PROFESSIONAL USE</p>	